

Polyurethane Whip Hose

fittings included

2010
NEW

- bright orange
- for use with jack hammers, chipping hammers, rock drills and other large pneumatic tools
- ½" male NPT swivels on each end
- abrasion resistant
- oil and grease resistant
- working pressure: **200 PSI** at 70°F
- strain relief steel spring bend restrictors



Hose ID	Length	Male NPT	Part #
½"	6'	½"	PFD068
½"	10'	½"	PFD108
½"	25'	½"	PFD125

☰
Air

Polyurethane Air Hose

fittings included

A sturdy, nylon-reinforced braid between the inner and outer tube allows for a higher working pressure.

- durable
- lightweight
- excellent flexibility
- oil resistant
- durometer: Shore A 85
- temperature range: **-40°F** to **155°F**
- working pressure at 70°F: **210 PSI**



Hose ID	Length	Male NPT	Part #
¼"	50'	¼"	450-4S
⅜"	50'	¼"	650-4S
⅜"	50'	⅜"	650-6S

Polyurethane Self-Storing Air Hose

fittings included

- extremely flexible - resists kinking
- impervious to abrasions, heat and oil
- superior elasticity and coil memory
- blue
- Polyurethane working pressure: **125 PSI** at 70°F
- both ends swivel



Hose ID	Length	Male NPT	Part #
¼"	10'	¼"	PU1410
¼"	15'	¼"	PU1415
¼"	25'	¼"	PU1425
⅜"	15'	⅜"	PU3815
⅜"	20'	⅜"	PU3820
⅜"	25'	⅜"	PU3825
⅜"	50'	⅜"	PU3850
½"	15'	½"	PU1215

Repair Kits

Tubing Size		Size	Type	Part #
ID	OD			
¼"	⅜"	¼"	swivel male	PSM0404
⅜"	9/16"	¼"	swivel male	PSM0604