


Imported Brass Ball Valves

- For control of air, water, oil and gas in hose or pipe lines. For other services, please contact the factory.
- rated to **600 PSI WOG; 150 PSI WSP**
- forged brass bodies
- blow-out proof stems
- PTFE seats, seals and thrust washers
- chrome-plated brass balls and plated steel handles
- maximum temperature **366°F**

- Underwriters, Factory Mutual, American Gas Association and Canadian Gas Association approved
- NSF61 approved




female NPT x female NPT



Size	Port Type	Brass	
		Part #	
1/4"	full	FBV25	
3/8"	full	FBV38	
1/2"	full	FBV50	
3/4"	full	FBV75	
1"	full	FBV100	
1 1/4"	full	FBV125	
1 1/2"	full	FBV150	
2"	full	FBV200	

female NPT x female NPT



Size	Port Type	Brass	
		Part #	
2 1/2"	full	FBV250	
3"	full	FBV300	
4"	full	FBV400	

female NPT x female NPT

Size	Port Type	Brass	
		Part #	
1/2"	standard	BV50	
3/4"	standard	BV75	
1"	standard	BV100	
1 1/4"	standard	BV125	
1 1/2"	standard	BV150	
2"	standard	BV200	

- For control of air, water, oil and gas in hose or pipe lines. For other services, please contact the factory.
- rated to **600 PSI WOG; 150 PSI WSP**
- forged brass bodies
- blow-out proof stems
- PTFE seats, seals and thrust washers
- chrome-plated brass balls and plated steel handles
- maximum temperature **366°F**

female NPT x female NPT



Size	Port Type	Brass	
		Part #	
1/2"	full	FBVI50	
3/4"	full	FBVI75	
1"	full	FBVI100	
1 1/4"	full	FBVI125	
1 1/2"	full	FBVI150	
2"	full	FBVI200	


- For control of air, water, oil and gas in hose or pipe lines. For other services, please contact the factory.
- rated to **600 PSI WOG; 150 PSI WSP**
- blow-out proof stems
- PTFE seats, double O-ring stem packing
- chrome-plated brass ball
- maximum temperature **366°F**
- Underwriters approved

Mini Ball Valves

- rated to **150 PSI**
- nickel plated brass body
- Teflon® seats and Buna-N stem seal
- blow-out proof stem
- maximum temperature **150°F**



female NPT x female NPT



Size	Port Type	Brass	
		Part #	
1/8"	standard	MBV12	
1/4"	full	MBV25	
3/8"	full	MBV38	
1/2"	standard	MBV50	