

Swivel with Ball Bearing (BKLK) Self-Locking Hook

- Ball bearing allows hook to swivel under load
- Latch closes automatically under load.
- Hook will not open when under load.
- Ball bearing allows hook to swivel under load
- Yoke allows attachment to chain, wire rope, or synthetic slings
- Stainless steel spring release trigger will only operate when hook is unloaded
- Full traceability
- Proof tested to 2 ½ times working load limit

MODEL	CHAIN SIZE	GRADE	WORKING LOAD LIMIT	DIMENSIONS (INCHES)								WEIGHT lbs
	inches			* (Lbs) at 90°	L	B	C	E	F	G	H	
BKLK-6-10	7/32	100	2,700	5.9	1.1	0.94	1.3	0.43	0.59	0.83	1.5	
BKLK-7/8-10	9/32	100	4,300	7.2	1.5	1.1	1.5	0.47	0.67	1.0	2.6	
BKLK-7/8-10	5/16	100	5,700	7.2	1.5	1.1	1.5	0.47	0.67	1.0	2.6	
BKLK-10-10	3/8	100	8,800	8.6	1.7	1.4	1.7	0.59	0.83	1.2	4.2	
BKLK-13-10	1/2	100	15,000	11.1	2.1	1.8	1.9	0.75	1.2	1.5	8.4	
BKLK-16-10	5/8	100	22,600	13.3	2.4	2.5	2.4	0.87	1.5	1.9	15.9	
BKLK-18/20-10	3/4	100	35,300	14.4	2.7	2.3	2.9	1.0	1.7	2.5	24.9	

*Design factor 4:1 Proof tested and certified.

**Grade 100 hooks have recessed trigger.

